

800 Watt 1-Way PA Loudspeaker / sub woofer

FX - 20

Applications

The FX-20 integrates with other loudspeakers to build an expandable total system.

Applications include:

Ballroom Events
Corporate Events
Band PA



BostonAudio FX-20

Physical

LF Subsystem	1x 15"-in, ventd
Configuration	1-Way, full range, dual purpos
PoweringPassive	LF crossove
Cabinet Type (shape)	Irregular pentagon (floor monitor)

Performance

Frequency Response (1 Watt @ 1m)	30 Hz to 170 kHz
Axial Sensitivity (dB SPL, 1 Watt @ 1m)	125
Impedance (Ohms)	8
Power Handling, AES Standard (Watts)	Full Range 800
Calculated Maximum Output (dB SPL @ 1m)	Peak 1600
Nominal Coverage Angle, -6 dB Points (degrees)	Conical 90
Recommended High-Pass Frequency	24 dB/Octave40 Hz

Specifications

Dimensions	595 mm x 885 mm x 685 mm
Weight	75 kg
Enclosure	Multi-ply hardwood
Finish	Black textured
Protective	Grille Powder-coated hex-stamped steel,black mesh screen
Rigging	Aluminum end plates on top and bottom with metric M10 threaded points; integral 1-1/2" (38 mm) pole mount receptacle on bottom

High-power 800 - Watt 1-way PA sound reinforcement speaker/floor monitor for live and playback applications

Exceptional sound quality, wide frequency bandwidth and extensive dynamic range

Extremely powerful long-excursion driver provides incredibly deep bass and acoustic power

Additional Line output allows linking of additional speaker systems

Ergonomically shaped handles for easy carrying and setup

Rugged steel grill for optimal speaker protection

Versatile enclosure profile allows different positioning:

High-quality components and exceptionally rugged construction ensure long life